

# Hot Streak

52" / TYPE II / 20 oz.    **LOW VOC**    **RECYCLED CONTENT**

**PHYSICAL PROPERTIES**

Weight      20 oz. PLY/620   G/PLM      13.3 oz. PSY/451   G/PSM  
Width      52"/132 cm  
Backing      Osnapburg  
Match      Straight, match

Custom colors, weights, and micro venting available

Meets or exceeds Federal Specification CCC-W-408D

**FIRE SAFETY**

- Class "A" Fire rated – Tested in accordance with ASTM E-84 Tunnel Test
- Passes Class "A" NFPA 101 Life Safety Code
- Passes NFPA 286 Corner Burn Test
- Tested in accordance with CAN/ULC S102.2

See website or contact us for additional results

**ENVIRONMENT & HEALTH**

- Contains 10% recycled content (varied blend of pre-consumer and remanufactured material)
- Certified to NSF/ANSI 342 Sustainability Assessment; ask distributor for details
- Meets California section 01350 IAQ test requirements for wallcovering
- Complies with USGBC LEED v4 Criteria, under Indoor Environmental Quality (CDPH/EHLB/Standard Method Version 1.1, 2010)

**WARRANTY**

5 year warranty against manufacturing defects. Additional information is available at [genonwallcovering.com](http://genonwallcovering.com)



**W2-HS-01** ROLL THE DICE